



Part No	Material	H (in)	E (in)	L (in)	W (in)	Weight (lbs)
416590	AISI 304	2.36	0.81	20.87	7.87	6.61
416591	AISI 304	2.36	0.81	32.68	7.87	8.86
416592	AISI 304	2.36	0.81	40.55	7.87	10.45
416593	AISI 304	2.36	0.81	48.43	7.87	11.95
416594	AISI 304	2.36	0.81	60.24	7.87	14.29
416595	AISI 304	2.36	0.81	79.92	7.87	17.99
416614	AISI 304	2.17	0.81	12.99	11.81	6.02
416615	AISI 304	2.36	0.81	24.80	11.81	8.51
416616	AISI 304	2.36	0.81	40.55	11.81	13.01
416617	AISI 304	2.36	0.81	60.24	11.81	18.08
416618	AISI 304	2.36	0.81	79.92	11.81	23.15
416619	AISI 304	2.76	0.81	119.29	11.81	34.61
416620	AISI 304	3.15	0.81	158.66	11.81	46.74
416642	AISI 304	2.36	1.20	16.93	15.75	8.73
416643	AISI 304	2.36	1.20	24.80	15.75	11.33
416644	AISI 304	2.36	1.20	32.68	15.75	13.98
416654	AISI 304	2.56	1.20	20.87	19.69	13.12
416655	AISI 304	2.56	1.20	32.68	19.69	18.45
416656	AISI 304	2.56	1.20	40.55	19.69	22.07

Part No	Material	H (in)	E (in)	L (in)	W (in)	Weight (lbs)
416608	AISI 316L	2.36	0.81	20.87	7.87	6.61
416609	AISI 316L	2.36	0.81	32.68	7.87	8.86
416610	AISI 316L	2.36	0.81	40.55	7.87	10.45
416611	AISI 316L	2.36	0.81	48.43	7.87	11.95
416612	AISI 316L	2.36	0.81	60.24	7.87	14.29
416613	AISI 316L	2.36	0.81	79.92	7.87	17.99
416628	AISI 316L	2.17	0.81	12.99	11.81	6.02
416629	AISI 316L	2.36	0.81	24.80	11.81	8.51
416630	AISI 316L	2.36	0.81	40.55	11.81	13.01
416631	AISI 316L	2.36	0.81	60.24	11.81	18.08
416632	AISI 316L	2.36	0.81	79.92	11.81	23.15
416633	AISI 316L	2.76	0.81	119.29	11.81	34.61
416634	AISI 316L	3.15	0.81	158.66	11.81	46.74
416648	AISI 316L	2.36	1.20	16.93	15.75	8.73
416649	AISI 316L	2.36	1.20	24.80	15.75	11.33
416650	AISI 316L	2.36	1.20	32.68	15.75	13.98
416660	AISI 316L	2.56	1.20	20.87	19.69	13.12
416661	AISI 316L	2.56	1.20	32.68	19.69	18.45
416662	AISI 316L	2.56	1.20	40.55	19.69	22.07

Specification Clause

ACO Hygienic Floor Trough. Overall length and height varies, see tables. Made from 16ga (1.5mm) AISI 304 or AISI 316L, pickle passivated finish. Used with 10" Floor Drains. Number of concrete anchors and adjustable leveling feet varies by channel length. Multiple grate options available. Certified to NSF/ANSI/3-A Standard 14159-1.

ACO recommends checking local plumbing codes prior to installation.

ACO Polymer Products, Inc.

Northeast Sales Office
 9470 Pinecone Dr.
 Mentor, OH 44060
 Tel: (440) 639-7230
 Toll Free: (800) 543-4764
 Fax: (440) 639-7235

West Sales Office
 825 W Beechcraft St.
 Casa Grande, AZ 85122
 Tel: (520) 421-9988
 Toll Free: (866) 809-4506
 Fax: (520) 421-9899

Southeast Sales Office
 4211 Pleasant Road
 Fort Mill, SC 29708
 Tel: (800) 543-4764
 Toll Free: (800) 543-4764
 Fax: (803) 802-1063

Follow us on



Electronic Contact:
 info@acousa.com
 www.acobuildingdrainage.us



May 2016 ACO Polymer Products, Inc. This information is believed to be accurate but it is not guaranteed to be so. We cannot assume liability for results that buyer obtains with our products since conditions of use are beyond the control of the company. It is the customer's responsibility to evaluate suitability and safety of product for his own use. ACO Polymer Products, Inc. reserves the right to change the product and specifications without notice.