ACO PERFORATED GRATING, W218-L218-H30

U
0
•••
U
ш
2
0
f
u
n
0
• •
U
5
ifi
J
0
P
S
-
C
1

	a_								, N	ϑ	-@-
Ī											
8.58in[218mm] 0.28in[7mm]											
			\square								
						\blacksquare					
								\square			
Ī											
<u> </u>	<u>d</u>								/	y _	-1
				•		Bin[7mi				1 18in[30mm]	
					8.58i	n[218n	nm]			Zin[2	
										+	-
											1
											1

Part no.	Material	Weight Ibs.	Intake sq in.	ASME Load Class
408097	AISI 304	2.8	9.2	Light Duty
408197	AISI 316L	2.8	9.2	Light Duty

Specification Clause

Used with ACO 10" Floor Drains. Made from AISI 304 or AISI 316L. Load class per ASME A112.6.3, section 5.

ACO recommends checking local plumbing codes prior to installation.

ACO Polymer Products, Inc.

Acto Polymer Product 9470 Pinecone Dr. Mentor, OH 44060 Tel: (440) 639-7230 Toll Free: (800) 543-4764 Fax: (440) 639-7235 r, IniC. West Sales Office 825 W Beechcraft St. Casa Grande, AZ 85122 Tel: (520) 421-9988 Toll Free: (866) 809-4506 Fax: (520) 421-9899 Southeast Sales Office 4211 Pleasant Road Fort Mill, SC 29708 Tel: (800) 543-4764 Toll Free: (800) 543-4764 Fax: (803) 802-1063



SPEC Z ACOO

May 2016 ACO Polymer Products, Inc. This information is believed to be accurate but it is not guaranteed to be so. We cannot assume liability for results that buyer obtains with our products since conditions of use are beyond the control of the company. It is the customer's responsibility to evaluate suitability and safety of product for his own use. ACO Polymer Products, Inc. reserves the right to change the product and specifications without notice.