



Part No	Material	H (in)	L (in)	Weight (lbs)
415932	AISI 304	2.76	19.69	5.93
415933	AISI 304	2.95	19.69	6.11
415934	AISI 304	3.15	19.69	6.28
415935	AISI 304	3.54	19.69	6.61
415936	AISI 304	3.94	19.69	6.94
415937	AISI 304	4.33	19.69	7.30
415938	AISI 304	4.72	19.69	7.63

Part No	Material	H (in)	L (in)	Weight (lbs)
415977	AISI 316L	2.76	19.69	5.93
415978	AISI 316L	2.95	19.69	6.11
415979	AISI 316L	3.15	19.69	6.28
415980	AISI 316L	3.54	19.69	6.61
415981	AISI 316L	3.94	19.69	6.94
415982	AISI 316L	4.33	19.69	7.30
415983	AISI 316L	4.72	19.69	7.63

Specification Clause

ACO Slot 20 center outlets. Overall height varies, see tables. Used with ACO 8" Floor Drains. Made from 16ga (1.5mm) AISI 304 or AISI 316L, pickle passivated finish. All channels provided with NBR seal and connection bolts on one side. Multiple grate options available.

ACO recommends checking local plumbing codes prior to installation.

ACO Polymer Products, Inc.

Northeast Sales Office 9470 Pinecone Dr. Mentor, OH 44060 Tel: (440) 639-7230 Toll Free: (800) 543-4764 Fax: (440) 639-7235 West Sales Office 825 W Beechcraft St. Casa Grande, AZ 85122 Tel: (520) 421-9988 Toll Free: (866) 809-4506 Fax: (520) 421-9899

Southeast Sales Office 4211 Pleasant Road Fort Mill, SC 29708 Tel: (800) 543-4764 Toll Free: (800) 543-4764 Fax: (803) 802-1063 Follow us on

Electronic Contact:
info@acousa.com
www.acobuildingdrainage.us



May 2016 ACO Polymer Products, Inc. This information is believed to be accurate but it is not guaranteed to be so. We cannot assume liability for results that buyer obtains with our products since conditions of use are beyord the control of the company. It is the customer's responsibility to evaluate suitability and safety of product for his own use. ACO Polymer Products, Inc. reserves the right to change the product and specifications without notice.